

Technical Specification

Serge Ferrari 

Stamoid Smart I and 2

- Waterproof and Breathable
- Easy to Clean
- Extreme Resistance to UV and Bad Weather
- Resistant to Extreme Temperatures
- Insensitive to oil, cream and polluted environments
- Lightweight and Compact
- Top Performance, Top Comfort

	Smart I (F4160)	Smart 2 (F3960)
Coating	I Side	2 Sides
Base Cloth	Polyester 280/550 dTex	Polyester 280/550 dTex
Weight	280 gr/m ² (8.2 oz/sqyd)	340 gr/m ² (10 oz/sqyd)
Width	250cm - 98.4in	250cm - 98.4in
Thickness	0.30mm – 300 microns	0.30mm – 300 microns
Roll Lengths	30 linear metres	30 linear metres
Tensile Strength	WARP - 125 daN/ 5cm	WARP - 125 daN/ 5cm
	WEFT - 140 daN/ 5cm	WEFT - 150 daN/ 5cm
Tear Strength	WARP – 14 daN	WARP – 14 daN
	WEFT – 30 daN	WEFT – 30 daN
Flexing Resistance	100 000	100 000
UV Filtration	UPF 50+	UPF 50+
Mould Resistance	Grade/Degree 0, excellent	Grade/Degree 0, excellent
Resistant to Water Penetration	>700cm	>700cm
Breathability	50g/m ² /24h	38g/m ² /24h
Colour Light Fastness	≥7	≥7
Extreme use Temperatures	-50 °C / +120°C	-50 °C / +120°C



PLEASE NOTE:

For care and cleaning Instructions, please contact Kayospruce Ltd.
Colours may vary slightly from different batches. Please check colour before cutting cloth as no claim will be accepted on colour variance. Avoid condensation from heat and humidity.