

Technical Specification

Serge Ferrari

Stamskin Zen (F4350)

- Exceptional Abrasion Resistance
- Specific treatment for hygiene and upkeep
- 100% Recyclable
- Large range of colours
- Waterproof

- Improved protection against stains and greasy matter without affecting the composites flexibility
- Multi-Layer coating
- New high-performance
- High flexibility and freedom of shape

Fabric Details

		M. L. I.
Composition		Multi-layer composition
Specific Formulation		Phtalate content ,0.1%
Base Cloth		Polyester Jersey
Weight		780 gr/m² (23 oz/sqyd)
Width		140cm
Thickness		0.8 mm – 1.0 mm
Roll Lengths		20 linear metres
Tensile Strength		WARP – >440N/5cm
		WEFT – >280N/5cm
Tear Resistance		WARP - >25N
		WEFT - >15N
Elongation Unde	r Load 125N/5cm	WARP – >35%
		WEFT – >55%
Abrasion Resistance		>120,000 - no worse than very slight damage
Flexing Resistance (no damage, cycles)		400,000
Cytotoxicity		Complies (reactivity benign or less)
Skin Irritation and Sensitivity		No reaction
Extreme Working Temperatures		-20 °C / +70 °C
Fire Ratings	-	IMO-MSC-307(88) (2010 FTP Code) Annex 1 part 8
		EN 1021.1 – 1021.2
Warranty		5 years from date of Invoice
		See T+C's



PLEASE NOTE:

For care and cleaning Instructions, please contact Kayospruce Ltd.

Colours may vary slightly from different batches. Please check colour before cutting cloth as no claim will be accepted on colour variance. Avoid condensation from heat and humidity.